

BAScontrol22C

BACnet/IP Sedona Field Controller

| | | | HE COM CHASSES |
|---------------|-------------------|---------------------------|--|
| un | UB | 601 | 24 VDC s10% 4W 24 VBC 110% ERA 42-43 1 881 DCs w AC 80 COM: 30 COM or AC 90 |
| 012 | | 812 | COM: DC COM or AC UD Class 2 Circuits-Dely |
| | UD | 813 | |
| ute | | 834 | BAScontrol22 |
| A01 | 801 | 805 | CONTEMPORARY |
| 402 | | 806 | Certinols |
| NO3 | . 803 | Defect + IAL ING. ALAM/24 | |
| 101 | | toot If Chief Based If C | ····· |
| A01 A02 A03 A | 04 801 802 803 80 | 04 805 806 + | -tan |

BACnet Protocol Implementation Conformance Statement (Annex A)

| rols |
|------|
| |
| |
| |

Applications Software Version: 1.2.28 Firmware Revision: 3.1.2 BACnet Protocol Revision: 3

Product Description: BACnet/IP compliant 22-point field controller or remote I/O that allows a direct connection to Ethernet without the need of a BACnet router.

BACnet Standardized Device Profile (Annex L):

BACnet Operator Workstation (B-OWS)

BACnet Building Controller (B-BC)

BACnet Advanced Application Controller (B-AAC)

BACnet Application Specific Controller (B-ASC) BACnet Smart Sensor (B-SS)

BACnet Smart Actuator (B-SA)

List all BACnet Interoperability Building Block Supported (Annex K):

| DS-RP-B Data Sharing — ReadProperty – A,B |
|--|
| DS-WP-B Data Sharing — WriteProperty – A,B |
| DS-RPM-B Data Sharing — ReadPropertyMultiple – B |
| DS-COV-B Data Sharing — ChangeOfValue – B |

DM-DDB-B Device Management — Dynamic Device Binding – B DM-DOB-B Device Management — Dynamic Object Binding – B DM-DCC-B Device Management — Device Communication Control – B DM-TS-B Device Management — Time Synchronization – B

MS/TP slave (Clause 9), baud rate(s):

LonTalk, (Clause 11), medium:

Point-To-Point, EIA 232 (Clause 10), baud rate(s):

Point-To-Point, modem, (Clause 10), baud rate(s):

Segmentation Capability:

Able to transmit segmented messages Window Size: Able to receive segmented messages

Window Size:

Standard Object Types Supported:

| Object Type Supported | Can Be Created Dynamically | Can Be Deleted Dynamically |
|-----------------------|----------------------------|----------------------------|
| Analog Input | No | No |
| Analog Output | No | No |
| Analog Value | No | No |
| Binary Input | No | No |
| Binary Output | No | No |
| Binary Value | No | No |
| Device | No | No |

No optional properties are supported.

Data Link Layer Options:

BACnet IP, (Annex J)

□ ISO 8802-3, Ethernet (Clause 7) ANSI/ATA 878.1, EIA-485 ARCNET (Clause 8), baud rate(s):

MS/TP master (Clause 9), baud rate(s):

Device Address Binding:

Is static device binding supported? (This is currently necessary for two-way communication with MS/TP slaves and certain other

Other:

devices.)

Networking Options:

Router, Clause 6 – List all routing configurations, e.g., ARCNET-Ethernet-MS/TP, etc.

| | Annex | H, BACnet | Tunnelling | Router over IP |
|---|-------|-----------|------------|----------------|
| _ | | | | |

🖾 No

BACnet/IP Broadcast Management Device (BBMD)

| Does the BBMD support registrations by Foreign Devices? | _ Yes | 🗌 No |
|---|-------|------|
|---|-------|------|

Character Sets Supported:

| Indicating support for | multiple character sets does not imply that | they can all be supported simultaneously |
|------------------------|---|--|
| 🖾 ANSI X3.4 | □ IBM [™] /Microsoft [™] DBCS | 🔲 ISO 8859-1 |

□ IBM[™]/Microsoft[™] DBCS □ ISO 10646 (UCS-4) □ ISO 10646 (UCS-2)

| 150 8859-1 |
|------------|
| JIS C 6226 |

If this product is a communication gateway, describe the types of non-BACnet equipment/network(s) that the gateway supports: No gateway support.